

Lube1TM Premium LV-ATF **NEW!**

Lube1TM Premium LV-ATF is a 100% fully-synthetic automatic transmission fluid of the newest generation with reduced viscosity. It meets and exceeds the requirements of the most recent 7-, 8- and 9-speed automatic transmissions. Lube1TM Premium LV-ATF guarantees reliable lubrication, even at extreme temperatures (up to 290°C over 30 h).

Description

Lube1TM Premium ATF is suitable for 8- and 9-speed automatic transmissions that require a low-viscosity ATF in cars and light utility vehicles. Workshops require thanks to Lube1TM Premium LV-ATF only one low-viscosity ATF for 7-, 8- and 9-speed automatic transmissions and expensive special-purpose oils. This simplifies work and cuts costs.

Attention! Lube1 Premium LV-ATF is not backwards compatible with older transmissions.

Application

Depending on the demands on the automatic transmission fluid-based vehicle, we recommend changing Lube1TM Premium LV-ATF at between 60'000 and 120'000 km¹ in order to guarantee long and trouble-free operation even if the vehicle is subject to heavy-duty requirements. In order to get the full benefits of its potential, however, it is worth carrying out a full oil change with the Lube1 TSD450E fluid exchange machine with flush program.

¹ Follow the OEM's recommendations

Advantages

- Replaces special-purpose oils for 7-, 8- and 9-speed automatic transmissions that require a low-viscosity ATF fluid
- Prevents mix-ups during oil changes
- Softens and modifies harsh gear shifts
- Extreme heat resistance
- Reduces the oil temperature in the automatic transmission significantly
- Prevents expensive transmission damage caused by overheating
- Prolongs the service life of automatic transmissions
- Simplifies purchasing and cuts costs
- Simplifies stock management

Technical specifications

Color, visual	light blue
Density at 20° C kg/m ³	842
Viscosity at 40° C mm ² /s	23,8
Flashpoint (COC)° C	195
Viscosity at 100° C mm ² /s	5,25
Viscosity index	161
Pourpoint °C	<-45

Performance Level

Recommendes for transmissions that require those performance levels:

- BMW ATF-3+
- Fuchs TITAN ATF 7134 FE
- LUKOIL ATF SYNTH M 15
- MB 236.15 ATF A 001 989 77 03
- MB 236.15 ATF A 001 989 78 03
- MB 236.16 ATF A 001 989 92 03
- Mobil ATF 134 FE
- Motul ATF 236.15
- RAVENOL ATF M 9-FE Serie
- Shell ATF 134FE
- Shell ATF D97
- Shell Spirax S6 ATF 134ME
- Syneco ATF M15
- Valvoline ATF Pro 236.15
- ZF Lifeguard 8+

Online-Oilfinder
www.lube1.eu/oilfinder

